

## DECLARATION OF PERFORMANCE

No. 00703

1. Unique identification code of the product-type: CERESIT MPS
2. Intended use/es: Sealant for facade for interior and exterior application - EN 15651-1: F-EXT-INT  
Sealant used for sealing glazing applications - EN 15651-2: G  
Sealant for joints in sanitary areas - EN 15651-3: S
3. Manufacturer: Henkel AG & Co. KGaA  
D-40191 Düsseldorf
4. Authorised representative: Not relevant
5. System/s of assessment and verification of constancy of performance: Type testing: System 3  
Reaction to fire: System 3
- 6a. Harmonised standard/s: EN 15651-1: 2012  
EN 15651-2: 2012  
EN 15651-3: 2012
- Notified body/ies: Type testing: FUNDACION TECNALIA RESEARCH & INNOVATION, 1292  
Reaction to fire: LGAI TECHNOLOGICAL CENTER, S. A./Applus, 0370
- 6b. European Assessment Document: Not relevant  
European Technical Assessment: Not relevant  
Technical Assessment Body: Not relevant  
Notified body/is: Not relevant
7. Declared performance/s:  
Conditioning: Method A  
Substrate: Glass without primer

Essential characteristics	Performance	System/s of assessment and verification of constancy of performance	Harmonised technical specification
Reaction to fire	Class E	System 3	EN 15651-1:2012
Release of chemicals dangerous to the environment and health	NPD	System 3	
Water tightness and air tightness			
Resistance to flow	≤ 3 mm		
Loss of volume	≤ 25 %		
Tensile properties (i.e. elongation) at maintained extension after water immersion	NF		
Durability	pass		

Conditioning: Method A  
Substrate: Glass without primer

Substrate: Glass without primer			
Essential characteristics	Performance	System/s of assessment and verification of constancy of performance	Harmonised technical specification
Reaction to fire	Class E	System 3	EN 15651-2:2012
Release of chemicals dangerous to the environment and health	NPD	System 3	
Water tightness and air tightness			
Loss of volume	≤ 40 %		
Vertical flow resistance	≤ 3 mm		
Adhesion/cohesion properties after exposure to heat, water and artificial light	NF		
Elastic recovery	≥ 60 %		
Durability	pass		

Conditioning: Method A  
Substrate: Glass without primer

Substrate: Glass without primer			
Essential characteristics	Performance	System/s of assessment and verification of constancy of performance	Harmonised technical specification
Reaction to fire	Class E	System 3	EN 15651-3:2012
Release of chemicals dangerous to the environment and health	NPD	System 3	
Water tightness and air tightness			
Resistance to flow	≤ 3 mm		
Loss of volume	≤ 20 %		
Tensile properties (i.e. elongation) after immersion in water at 23°C	≥ 25 %		
Microbiological growth	1		
Durability	pass		

8. Appropriate Technical Documentation and/or Specific Technical Documentation: Not relevant

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

Baptiste Chièze  
International Brand Manager  
(name and function)




(signature)

Dr. Bernhard Schöttmer  
Director Global Product Development  
(name and function)



(signature)

Düsseldorf, 12.02.2015  
(place and date of issue)

 1292, 0370	
Henkel AG & Co. KGaA, D-40191 Düsseldorf 14 00703  CERESIT MPS	
EN 15651-1: 2012  Sealant for facade for interior and exterior application - Type F-EXT-INT - Conditioning: Method A - Substrate: Glass without primer	
<b>Reaction to fire</b>	Class E
<b>Release of chemicals dangerous to the environment and health</b>	NPD
<b>Water tightness and air tightness</b>	
Resistance to flow	≤ 3 mm
Loss of volume	≤ 25 %
Tensile properties (i.e. elongation) at maintained extension after water immersion	NF
<b>Durability</b>	pass
EN 15651-2: 2012  Sealant used for sealing glazing applications - Type G - Conditioning: Method A - Substrate: Glass without primer	
<b>Reaction to fire</b>	Class E
<b>Release of chemicals dangerous to the environment and health</b>	NPD
<b>Water tightness and air tightness</b>	
Loss of volume	≤ 40 %
Vertical flow resistance	≤ 3 mm
Adhesion/cohesion properties after exposure to heat, water and artificial light	NF
Elastic recovery	≥ 60 %
<b>Durability</b>	pass
EN 15651-3: 2012  Sealant for joints in sanitary areas - Type S - Conditioning: Method A - Substrate: Glass without primer	
<b>Reaction to fire</b>	Class E
<b>Release of chemicals dangerous to the environment and health</b>	NPD
<b>Water tightness and air tightness</b>	
Resistance to flow	≤ 3 mm
Loss of volume	≤ 20 %
Tensile properties (i.e. elongation) after immersion in water at 23°C	≥ 25 %
Microbiological growth	1
<b>Durability</b>	pass