

DECLARATION OF PERFORMANCE

No. 00790

1. Unique identification code of the product-type: CERESIT LMN BROWN
2. Intended use/es: Sealant for facade for interior and exterior application (F-EXT-INT)
Sealant used for sealing glazing applications (G)
3. Manufacturer: Henkel AG & Co. KGaA
D-40191 Düsseldorf
4. Authorised representative: Not relevant
5. System/s of assessment and verification of constancy of performance: Type testing: System 3
Reaction to fire: System 4
- 6a. Harmonised standard/s: EN 15651-1: 2012
EN 15651-2: 2012
- Notified body/ies: Type testing: SKZ-TeConA GmbH, 1213
- 6b. European Assessment Document: Not relevant
European Technical Assessment: Not relevant
Technical Assessment Body: Not relevant
Notified body/is: Not relevant
7. Declared performance/s:

Conditioning: Method A

Substrate: Aluminium; without primer

Essential characteristics	Performance	System/s of assessment and verification of constancy of performance	Harmonised technical specification
Reaction to fire	Class F	System 4	EN 15651-1:2012
Release of chemicals dangerous to the environment and health	NPD	System 3	
Water tightness and air tightness			
Resistance to flow	≤ 3 mm		
Loss of volume	≤ 30 %		
Tensile properties (i.e. elongation) at maintained extension after water immersion]	NF		
Durability	pass		

Conditioning: Method A
Substrate: Glass; without primer

Substrate: Class, without primer			
Essential characteristics	Performance	System/s of assessment and verification of constancy of performance	Harmonised technical specification
Reaction to fire	Class F	System 4	EN 15651-2:2012
Release of chemicals dangerous to the environment and health	NPD	System 3	
Water tightness and air tightness			
Loss of volume	≤ 40 %		
Vertical flow resistance	≤ 3 mm		
Adhesion/cohesion properties after exposure to heat, water and artificial light	NF		
Elastic recovery	≥ 60 %		
Durability	pass		

8. Appropriate Technical Documentation and/or Specific Technical Documentation: Not relevant

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

Baptiste Chièze
International Brand Manager
(name and function)



(signature)


Dr. Bernhard Schöttmer
Director Global Product Development
(name and function)



(signature)

Düsseldorf, 22.08.2016
(place and date of issue)

Attachment

 1213	
Henkel AG & Co. KGaA, D-40191 Düsseldorf 14 00970 CERESIT LMN BROWN	
EN 15651-1: 2012 Sealant for facade for interior and exterior application - Type: F-EXT-INT - Conditioning: Method A - Substrate: Aluminium; without primer	
Reaction to fire	Class F
Release of chemicals dangerous to the environment and health	NPD
Water tightness and air tightness	
Resistance to flow	≤ 3 mm
Loss of volume	≤ 30 %
Tensile properties (i.e. elongation) at maintained extension after water immersion]	NF
Durability	pass
EN 15651-2: 2012 Sealant used for sealing glazing applications - Type: G - Conditioning: Method A - Substrate: Glass; without primer	
Reaction to fire	Class F
Release of chemicals dangerous to the environment and health	NPD
Water tightness and air tightness	
Loss of volume	≤ 40 %
Vertical flow resistance	≤ 3 mm
Adhesion/cohesion properties after exposure to heat, water and artificial light	NF
Elastic recovery	≥ 60 %
Durability	pass