



DECLARATION OF PERFORMANCE

No. 00978

- | | |
|---|--|
| 1. Unique identification code of the product-type: | By Pattex Silicon |
| 2. Intended use/es: | Sealant for joints in sanitary areas (S) |
| 3. Manufacturer: | Henkel AG & Co. KGaA
D-40191 Düsseldorf |
| 4. Authorised representative: | Not relevant |
| 5. System/s of assessment and verification of constancy of performance: | Type-testing: System 3
Reaction to fire: System 3 |
| 6a. Harmonised standard/s: | EN 15651-3: 2012 |
| Notified body/ies: | Type-testing: FUNDACION TECNALIA RESEARCH & INNOVATION, 1292
Reaction to fire : LGAI TECHNOLOGICAL CENTER, S. A./Applus, 0370 |
| 6b. European Assessment Document: | Not relevant |
| European Technical Assessment: | Not relevant |
| Technical Assessment Body: | Not relevant |
| Notified body/is: | Not relevant |
| 7. Declared performance/s: | |

Conditioning: Method A

Substrate: Glass; without primer

Essential characteristics	Performance	System/s of assessment and verification of constancy of performance	Harmonised technical specification
Reaction to fire	Class E	System 3	EN 15651-3: 2012
Release of chemicals dangerous to the environment and health	NPD	System 3	
Water tightness and air tightness			
Resistance to flow	≤ 3 mm		
Loss of volume	≤ 20 %		
Tensile properties (i.e. elongation) after immersion in water at 23°C	≥ 25 %		
Microbiological growth	1		
Durability	pass		

- | | |
|---|--------------|
| 8. Appropriate Technical Documentation and/or Specific Technical Documentation: | Not relevant |
|---|--------------|



The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

Simon Duggan-Hill
Global Steering Unit Head - ACG

(name and function)

(signature)

Dr. Bernhard Schöttmer
Director Global Product Development

(name and function)

(signature)

Düsseldorf, 25.7.2018

(place and date of issue)

Attachment

 1292, 0370	
Henkel AG & Co. KGaA D-40191 Düsseldorf 14 00978 By Pattex Silicon	
EN 15651-3: 2012 Sealant for joints in sanitary areas	
- Type	S
- Conditioning:	Method A
- Substrate:	Glass; without primer
Reaction to fire	Class E
Water tightness and air tightness	
Resistance to flow	≤ 3 mm
Loss of volume	≤ 20 %
Tensile properties (i.e. elongation) after immersion in water at 23°C	≥ 25 %
Microbiological growth	1
Durability	pass
www.henkel-dop.com	