

## DECLARATION OF PERFORMANCE

No. 01172

- |   |   |
|---|---|
| 1. Unique identification code of the product-type:                      | By Pattex Acrylic (01172)   |
| 2. Intended use/es:   | Sealant for facade for interior and exterior application (F-EXT-INT)            |
| 3. Manufacturer:  | Henkel AG & Co. KGaA<br>D-40191 Düsseldorf                                      |
| 4. Authorised representative:   | Not relevant  |
| 5. System/s of assessment and verification of constancy of performance: | Type-testing: System 3<br>Reaction to fire: System 3                            |
| 6a. Harmonised standard/s:  | EN 15651-1: 2012  |
| Notified body/ies:  | Type-testing: SKZ-TeConA GmbH, 1213<br>Reaction to fire : SKZ-TeConA GmbH, 1213 |
| 6b. European Assessment Document:                                       | Not relevant  |
| European Technical Assessment:  | Not relevant  |
| Technical Assessment Body:  | Not relevant  |
| Notified body/is:   | Not relevant  |
| 7. Declared performance/s:  |   |

Conditioning: Method B

Substrate: Aluminium; without primer

Essential characteristics	Performance	System/s of assessment and verification of constancy of performance	Harmonised technical specification
<b>Reaction to fire</b>	Class E	System 3	EN 15651-1: 2012
<b>Release of chemicals dangerous to the environment and health</b>	NPD	System 3	
<b>Water tightness and air tightness</b>			
Resistance to flow	≤ 3 mm		
Loss of volume	≤ 30 %		
Tensile properties (i.e. elongation) after immersion in water at 23°C	≥ 25 %		
<b>Durability</b>	pass		

- |   |              |
|---|--------------|
| 8. Appropriate Technical Documentation and/or Specific Technical Documentation: | Not relevant |
|---|--------------|



The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

Simon Duggan-Hill  
Global Steering Unit Head - ACG

---

(name and function)

(signature)

Dr. Bernhard Schöttmer  
Director Global Product Development

---


(name and function)

(signature)

Düsseldorf, 16.8.2018

---

(place and date of issue)

 1213	
Henkel AG & Co. KGaA D-40191 Düsseldorf 15 01172  By Pattex Acrylic (01172)	
EN 15651-1: 2012 Sealant for facade for interior and exterior application	
- Type	F-EXT-INT
- Conditioning:	Method B
- Substrate:	Aluminium; without primer
<b>Reaction to fire</b>	Class E
<b>Water tightness and air tightness</b>	
Resistance to flow	≤ 3 mm
Loss of volume	≤ 30 %
Tensile properties (i.e. elongation) after immersion in water at 23°C	≥ 25 %
<b>Durability</b>	pass
<a href="http://www.henkel-dop.com">www.henkel-dop.com</a>	