

## **DECLARATION OF PERFORMANCE**

No. 01191

Unique identification code of the

product-type:

UniBond Outdoor Window and Door Frame Sealant

2. Intended use/es: Sealant for facade for interior and exterior application - EN 15651-

1: F-EXT-INT

Not relevant

3. Manufacturer: Henkel AG & Co. KGaA D-40191 Düsseldorf

4. Authorised representative:

> System/s of assessment and verification of constancy of

performance:

Type testing: System 3 Reaction to fire: System 3

6a. Harmonised standard/s:

EN 15651-1: 2012 Notified body/ies:

Type testing: SKZ Testing GmbH, 1213 Reaction to fire: SKZ Testing GmbH, 1213

6b. European Assessment Document: European Technical Assessment:

Technical Assessment Body: Notified body/is:

Not relevant Not relevant Not relevant Not relevant

7. Declared performance/s:

Conditioning: Method A

Substrate: Aluminium; without primer

Essential characteristics	Performance	System/s of assessment and verification of constancy of performance	Harmonised technical specification
Reaction to fire	Class E	System 3	
Release of chemicals dangerous to the environment and health	NPD		
Water tightness and air tightness			
Resistance to flow	≤ 3 mm		EN 15651-1:2012
Loss of volume	≤ 10 %	System 3	
Tensile properties (i.e. elongation) at maintained extension after water immersion]	NF		
Durability	pass		

Appropriate Technical Documentation

and/or Specific Technical

Documentation:

Not relevant



The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

Baptiste Chièze	ze Dr. Bernhard Schöttmer	
International Brand Manager	Director Global Product Development	
(name and function)	(name and function)	
3/	13568	
(signature)	(signature)	
D	üsseldorf, 10.12.2015	
(1	place and date of issue)	



## Attachment

