

DECLARATION OF PERFORMANCE

No. 01199

- | | |
|---|--|
| 1. Unique identification code of the product-type: | UniBond General Purpose Silicone Sealant |
| 2. Intended use/es: | Sealant for facade for interior and exterior application - EN 15651-1: F-EXT-INT
Sealant for joints in sanitary areas - EN 15651-3: S |
| 3. Manufacturer: | Henkel AG & Co. KGaA
D-40191 Düsseldorf |
| 4. Authorised representative: | Not relevant |
| 5. System/s of assessment and verification of constancy of performance: | Type testing: System 3
Reaction to fire: System 3 |
| 6a. Harmonised standard/s: | EN 15651-1: 2012
EN 15651-3: 2012 |
| Notified body/ies: | Type testing: FUNDACION TECNALIA RESEARCH & INNOVATION,1292
Reaction to fire: LGAI TECHNOLOGICAL CENTER, S. A./Applus ,0370 |
| 6b. European Assessment Document: | Not relevant |
| European Technical Assessment: | Not relevant |
| Technical Assessment Body: | Not relevant |
| Notified body/is: | Not relevant |
| 7. Declared performance/s: | |
- Conditioning: Method [A]
Substrate: Glass; without primer

Essential characteristics	Performance	System/s of assessment and verification of constancy of performance	Harmonised technical specification
Reaction to fire	Class E	System 3	EN 15651-1:2012
Release of chemicals dangerous to the environment and health	NPD	System 3	
Water tightness and air tightness			
Resistance to flow	≤ 3 mm		
Loss of volume	≤ 25 %		
Tensile properties (i.e. elongation) at maintained extension after water immersion]	NF		
Durability	pass		

Conditioning: Method A
Substrate: Glass; without primer

Essential characteristics	Performance	System/s of assessment and verification of constancy of performance	Harmonised technical specification
Reaction to fire	Class E	System 3	EN 15651-3:2012
Release of chemicals dangerous to the environment and health	NPD	System 3	
Water tightness and air tightness			
Resistance to flow	≤ 3 mm		
Loss of volume	≤ 20 %		
[Tensile properties (i.e. elongation) after immersion in water at 23°C	≥ 25 %		
Microbiological growth	1		
Durability	pass		

8. Appropriate Technical Documentation and/or Specific Technical Documentation: Not relevant

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.


Signed for and on behalf of the manufacturer by:

Baptiste Chièze
International Brand Manager
(name and function)



(signature)


Dr. Bernhard Schöttmer
Director Global Product Development
(name and function)



(signature)

Düsseldorf, 07.12.2015

(place and date of issue)

<div style="text-align: center;">  1292, 0370 </div>	
<div style="text-align: center;"> Henkel AG & Co. KGaA, D-40191 Düsseldorf 16 01199 UniBond General Purpose Silicone Sealant </div>	
<div style="text-align: center;">EN 15651-1: 2012</div>	
<div style="text-align: center;">Sealant for facade for interior and exterior application</div>	
- Type F-EXT-INT - Conditioning: Method A - Substrate: Glass; without primer	
Reaction to fire	Class E
Release of chemicals dangerous to the environment and health	NPD
Water tightness and air tightness	
Resistance to flow	≤ 3 mm
Loss of volume	≤ 25 %
Tensile properties (i.e. elongation) at maintained extension after water immersion]	NF
Durability	pass
<div style="text-align: center;">EN 15651-3: 2012</div>	
<div style="text-align: center;">Sealant for joints in sanitary areas</div>	
- Type S - Conditioning: Method A - Substrate: Glass; without primer	
Reaction to fire	Class E
Release of chemicals dangerous to the environment and health	NPD
Water tightness and air tightness	
Resistance to flow	≤ 3 mm
Loss of volume	≤ 20 %
[Tensile properties (i.e. elongation) after immersion in water at 23°C	≥ 25 %
Microbiological growth	1
Durability	Pass