

DECLARATION OF PERFORMANCE

No. 01210

1. Unique identification code of the

product-type:

3.

UniBond Kitchen & Bathroom Easy Smooth Sealant

2. Intended use/es: Sealant for joints in sanitary areas - EN 15651-3: S

Manufacturer: Henkel AG & Co. KGaA

D-40191 Düsseldorf

4. Authorised representative: Not relevant

5. System/s of assessment and verification of constancy of

performance:

Type testing: System 3

Reaction to fire: System 3

6a. Harmonised standard/s: EN 15651-3: 2012

Notified body/ies: Type testing: SKZ Testing GmbH, 1213

Reaction to fire: SKZ Testing GmbH,1213

6b. European Assessment Document: Not relevant

European Technical Assessment: Technical Assessment Body:

Notified body/is:

Not relevant Not relevant Not relevant

7. Declared performance/s:

Conditioning: Method B

Substrate: Aluminium; without primer

Essential characteristics	Performance	System/s of assessment and verification of constancy of performance	Harmonised technical specification
Reaction to fire	Class E	System 3	
Release of chemicals dangerous	NPD		
to the environment and health			
Water tightness and air tightness			
Resistance to flow	≤ 3 mm	System 3	EN 15651-3:2012
Loss of volume	≤ 20 %		EN 13031-3.2012
[Tensile properties (i.e. elongation) after immersion in water at 23°C	≥ 25 %		
Microbiological growth	0		
Durability	pass		

8. Appropriate Technical Documentation

and/or Specific Technical

Documentation:

Not relevant



The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

Baptiste Chièze	Dr. Bernhard Schöttmer	
International Brand Manager	Director Global Product Development	
(name and function)	(name and function)	
3/	B522	
(signature)	(signature)	
	Düsseldorf, 07.12.2015	
(place and date of issue)		



Attachment



Henkel AG & Co. KGaA, D-40191 Düsseldorf 16 01210

UniBond Kitchen & Bathroom Easy Smooth Sealant

EN 15651-3: 2012

Sealant for joints in sanitary areas

TypeConditioning:Substrate: S Method B

- Substrate: Aluminium; without primer	
Reaction to fire	Class E
Release of chemicals dangerous to the	NPD
environment and health	
Water tightness and air tightness	
Resistance to flow	≤3 mm
Loss of volume	≤ 20 %
[Tensile properties (i.e. elongation) after	≥ 25 %
immersion in water at 23°C	
Microbiological growth	0
Durability	pass