



DECLARATION OF PERFORMANCE

No. 01217

1. Unique identification code of the product-type: UniBond One For All Universal
2. Intended use/es: Sealant for facade for interior and exterior application - EN 15651-1: F-EXT-INT
3. Manufacturer: Henkel AG & Co. KGaA
D-40191 Düsseldorf
4. Authorised representative: Not relevant
5. System/s of assessment and verification of constancy of performance: Type testing: System 3
Reaction to fire: System 3
- 6a. Harmonised standard/s: EN 15651-1: 2012
Notified body/ies: Type testing: FUNDACION TECNALIA RESEARCH & INNOVATION, 1292
Reaction to fire: FUNDACION TECNALIA RESEARCH & INNOVATION, 1292
- 6b. European Assessment Document: Not relevant
European Technical Assessment: Not relevant
Technical Assessment Body: Not relevant
Notified body/is: Not relevant
7. Declared performance/s:

Conditioning: Method A

Substrate: Aluminium; without primer

Essential characteristics	Performance	System/s of assessment and verification of constancy of performance	Harmonised technical specification
Reaction to fire	Class E	System 3	EN 15651-1:2012
Release of chemicals dangerous to the environment and health	NPD	System 3	
Water tightness and air tightness			
Resistance to flow	≤ 3 mm		
Loss of volume	≤ 10 %		
[Tensile properties (i.e. elongation) after immersion in water at 23°C	≥ 100 %		
Durability	pass		

8. Appropriate Technical Documentation and/or Specific Technical Documentation: Not relevant



The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

Baptiste Chièze
International Brand Manager

(name and function)

(signature)

Dr. Bernhard Schöttmer
Director Global Product Development

(name and function)

(signature)

Düsseldorf, 19.01.2016

(place and date of issue)

Attachment

 1292	
Henkel AG & Co. KGaA, D-40191 Düsseldorf 16 01217 UniBond One For All Universal	
EN 15651-1: 2012 Sealant for facade for interior and exterior application - Type: F-EXT-INT - Conditioning: Method A - Substrate: Aluminium; without primer	
Reaction to fire	Class E
Release of chemicals dangerous to the environment and health	NPD
Water tightness and air tightness	
Resistance to flow	≤ 3 mm
Loss of volume	≤ 10 %
[Tensile properties (i.e. elongation) after immersion in water at 23°C	≥ 100 %
Durability	pass