

DECLARATION OF PERFORMANCE

No. 01342

1. Unique identification code of the product-type: UniBond FT101
2. Intended use/es: Sealant for facade for interior and exterior application (F-EXT-INT)
3. Manufacturer: Henkel AG & Co. KGaA
4. Authorised representative: Not relevant
5. System/s of assessment and verification of constancy of performance: Type-testing: System 3
Reaction to fire: System 3
- 6a. Harmonised standard/s: EN 15651-1:2012
Notified body/ies: Type-testing: SKZ-TeConA GmbH, 1213
Reaction to fire : SKZ-TeConA GmbH, 1213
- 6b. European Assessment Document: Not relevant
European Technical Assessment: Not relevant
Technical Assessment Body: Not relevant
Notified body/ies: Not relevant
7. Declared performance/s:

Conditioning: Method A

Substrate: Aluminium; without primer

| Essential characteristics | Performance | System/s of assessment and verification of constancy of performance | Harmonised technical specification |
|--|-------------|---|------------------------------------|
| Reaction to fire | Class E | System 3 | EN 15651-1:2012 |
| Release of chemicals dangerous to the environment and health | NPD | System 3 | |
| Water tightness and air tightness | | | |
| Resistance to flow | ≤ 3 mm | | |
| Loss of volume | ≤ 10 % | | |
| Tensile properties (i.e. elongation) at maintained extension after water immersion | NF | | |
| Durability | pass | | |

8. Appropriate Technical Documentation and/or Specific Technical Documentation: Not relevant



The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

Baptiste Chièze
International Brand Manager

(name and function)

A handwritten signature in black ink, appearing to be "B. Chièze", written over a horizontal line.

(signature)

Dr. Bernhard Schöttmer
Director Global Product Development

(name and function)

A handwritten signature in black ink, appearing to be "B. Schöttmer", written over a horizontal line.

(signature)

Düsseldorf, 15.2.2017

(place and date of issue)

Attachment

| | |
|---|---------|
|  1213 | |
| Henkel AG & Co. KGaA 17 01342 UniBond FT101 | |
| EN 15651-1:2012 Sealant for facade for interior and exterior application - Type F-EXT-INT - Conditioning: Method A - Substrate: Aluminium; without primer | |
| Reaction to fire | Class E |
| Release of chemicals dangerous to the environment and health | NPD |
| Water tightness and air tightness | |
| Resistance to flow | ≤ 3 mm |
| Loss of volume | ≤ 10 % |
| Tensile properties (i.e. elongation) at maintained extension after water immersion | NF |
| Durability | pass |