

DECLARATION OF PERFORMANCE

No. 01561

1. Unique identification code of the

product-type:

UniBond Bath & Kitchen (01561)

2. Intended use/es:

Sealant for joints in sanitary areas (S)

3. Manufacturer:

Henkel AG & Co. KGaA D-40191 Düsseldorf

4. Authorised representative:

Not relevant

5. System/s of assessment and verification of constancy of

performance:

Type-testing: System 3 Reaction to fire: System 3

6a. Harmonised standard/s:

EN 15651-3:2012

Notified body/ies:

Type-testing: SKZ-TeConA GmbH, 1213 Reaction to fire: SKZ-TeConA GmbH, 1213

6b. European Assessment Document: European Technical Assessment: Technical Assessment Body:

Notified body/is:

Not relevant Not relevant Not relevant

7. Declared performance/s:

Conditioning: Method A

Substrate: Aluminium; without primer

Essential characteristics	Performance	System/s of assessment and verification of constancy of performance	Harmonised technical specification
Reaction to fire	Class E	System 3	
Release of chemicals dangerous to the environment and health	NPD		
Water tightness and air tightness			
Resistance to flow	≤ 3 mm		
Loss of volume	≤ 20 %		
Tensile properties (i.e. elongation) at maintained extension after water immersion	NF	System 3	EN 15651-3:2012
Microbiological growth	0		
Durability			
Tensile properties (i.e. elongation) at maintained extension after water immersion	NF		

 Appropriate Technical Documentation Not relevant and/or Specific Technical Documentation:



The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

Ian Lapsley Global Head of Marketing ACG I	Dr. Michael Frank Director Global Product Development		
(name and function)	(name and function)		
Copsien.	Mulicul Jung		
(signature)	(signature)		

Düsseldorf, 27.10.2022

(place and date of issue)



Attachment



1213

Henkel AG & Co. KGaA D-40191 Düsseldorf 20 01561

UniBond Bath & Kitchen (01561)

EN 15651-3:2012			
Sealant for joints in sanitary areas			
Reaction to fire	Class E		
Water tightness and air tightness			
Resistance to flow	≤ 3 mm		
Loss of volume	≤ 20 %		
Tensile properties (i.e. elongation) at maintained	NF		
extension after water immersion			
Microbiological growth	0		
Durability			
Tensile properties (i.e. elongation) at maintained	NF		
extension after water immersion			
www.henkel-dop.com			