

DECLARATION OF PERFORMANCE

No. 01771

1. Unique identification code of the product-type: UniBond Indoor General Purpose Sealant (01771)
2. Intended use/es: Sealant for facade for interior and exterior application (F-EXT-INT)
Sealant for joints in sanitary areas (S)
3. Manufacturer: Henkel AG & Co. KGaA
D-40191 Düsseldorf
4. Authorised representative: Not relevant
5. System/s of assessment and verification of constancy of performance: Type-testing: System 3
Reaction to fire: System 3
- 6a. Harmonised standard/s: EN 15651-1:2012
EN 15651-3:2012
- Notified body/ies: Type-testing: FUNDACION TECNALIA RESEARCH & INNOVATION, 1292
Reaction to fire : LGAI TECHNOLOGICAL CENTER, S. A./Applus, 0370
- 6b. European Assessment Document: Not relevant
European Technical Assessment: Not relevant
Technical Assessment Body: Not relevant
Notified body/is: Not relevant
7. Declared performance/s:

Conditioning: Method A
Substrate: Glass; without primer

Essential characteristics	Performance	System/s of assessment and verification of constancy of performance	Harmonised technical specification
Reaction to fire	Class E	System 3	EN 15651-1:2012
Release of chemicals dangerous to the environment and health	NPD	System 3	
Water tightness and air tightness			
Resistance to flow	≤ 3 mm		
Loss of volume	≤ 25 %		
Tensile properties (i.e. elongation) at maintained extension after water immersion	NF		
Durability			
Tensile properties (i.e. elongation) at maintained extension after water immersion	NF		

Conditioning: Method A
Substrate: Glass; without primer


substrate: Class: without primer			
Essential characteristics	Performance	System/s of assessment and verification of constancy of performance	Harmonised technical specification
Reaction to fire	Class E	System 3	EN 15651-3:2012
Release of chemicals dangerous to the environment and health	NPD	System 3	
Water tightness and air tightness			
Resistance to flow	≤ 3 mm		
Loss of volume	≤ 20 %		
Tensile properties (i.e. elongation) at maintained extension after water immersion	NF		
Microbiological growth	1		
Durability			
Tensile properties (i.e. elongation) at maintained extension after water immersion	NF		

8. Appropriate Technical Documentation Not relevant
and/or Specific Technical Documentation:

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

Ian Lapsley
Global Head of Marketing ACG I
(name and function)




(signature)

Dr. Michael Frank
Director Global Product Development
(name and function)



(signature)

Düsseldorf, 25.10.2022
(place and date of issue)

 1292, 0370	
Henkel AG & Co. KGaA D-40191 Düsseldorf 23 01771 UniBond Indoor General Purpose Sealant (01771)	
EN 15651-1:2012 Sealant for facade for interior and exterior application	
Reaction to fire	Class E
Water tightness and air tightness	
Resistance to flow	≤ 3 mm
Loss of volume	≤ 25 %
Tensile properties (i.e. elongation) at maintained extension after water immersion	NF
Durability	
Tensile properties (i.e. elongation) at maintained extension after water immersion	NF
EN 15651-3:2012 Sealant for joints in sanitary areas	
Reaction to fire	Class E
Water tightness and air tightness	
Resistance to flow	≤ 3 mm
Loss of volume	≤ 20 %
Tensile properties (i.e. elongation) at maintained extension after water immersion	NF
Microbiological growth	1
Durability	
Tensile properties (i.e. elongation) at maintained extension after water immersion	NF
www.henkel-dop.com	