

DECLARATION OF PERFORMANCE

No. 00431

- | | |
|---|--|
| 1. Unique identification code of the product-type: | Ceresit Ceretherm Visage |
| 2. Intended use/es: | External Thermal Insulation System with rendering |
| 3. Manufacturer: | Henkel Polska Operations Sp. z o.o., ul. Domaniewska 41, 02-672 Warszawa |
| 4. Authorized representative: | Not relevant |
| 5. System/s of assessment and verification of constancy of performance: | System 2+ |
| 6a. Harmonized standard/s: | Not relevant |
| 6b. European Assessment Document: | EAD 040083-00-0404 |
| European Technical Assessment: | ETA 11/0395 z 30/06/2023 |
| Technical Assessment Body: | Instytut Techniki Budowlanej |
| Notified body/ies: | Instytut Techniki Budowlanej, nr 1488, Zakład Certyfikacji 1488-CPR-0370/Z |
| 7. Declared performance/s: | |

No	Essential characteristics	Performance	System/s of AVCP	Harmonised technical specification
1	Reaction to fire ETICS CERESIT CERETHERM VISAGE with EPS boards (reaction to fire Class E) and rendering system: - Adhesive: Ceresit CT83 - Base coat: Ceresit CT85 - Finishing coats: Ceresit CT77, Ceresit CT 177, Ceresit CT710 Super, Ceresit CT720, Ceresit CT760 (with the key coat) - Decorative coats: Ceresit CT721 (with Ceresit CT720) ETICS CERESIT CERETHERM VISAGE with EPS boards (reaction to fire Class E) and rendering system: - Adhesive: Ceresit CT83 - Base coat: Ceresit CT85 - Finishing coats: Ceresit CT710, Ceresit CT730 (with the key coat) - Decorative coats: Ceresit CT740, Ceresit CT750	B – s1, d0 C – s2, d0	System 2+	EAD 040083-00-0404
2	Water absorption after 1 hour Base coat Ceresit CT85 Water absorption after 24 hours Base coat Ceresit CT85 Water absorption after 24 hours Rendering system: Base coat Ceresit CT85 (with the key coat) and: Ceresit CT60 0,5mm, Ceresit CT710, Ceresit CT720 + Ceresit CT721, Ceresit CT730, Ceresit CT77, Ceresit CT177, Ceresit CT710 Super, Ceresit CT760	< 1,0 kg/m² < 0,5 kg/m²		
3	Condition after thermal and humid cycles	Resistant		
4	Condition after freeze and thaw cycles	Resistant		
5	Impact resistance Rendering system: Base coat Ceresit CT85 (with the key coat) and: Ceresit CT720 + Ceresit CT721, Ceresit CT710 Super, Ceresit CT760 Ceresit CT710, Ceresit CT730, Ceresit CT60 0,5mm, Ceresit CT60 0,5mm + Ceresit CT740, Ceresit CT60 0,5mm + Ceresit CT750, Ceresit CT77, Ceresit CT177	Category III Category II Category I		
6	Water vapour permeability Rendering system: Base coat Ceresit CT85 (with the key coat) and: Ceresit CT60 0,5mm, Ceresit CT60 0,5mm + Ceresit CT740, Ceresit CT60 0,5mm + Ceresit CT750, Ceresit CT710, Ceresit CT710 Super, Ceresit CT720 + Ceresit CT721, Ceresit CT730, Ceresit CT760, Ceresit CT77, Ceresit CT177	≤ 1,0m		
7	Dangerous substances	see MSDS		
8	Bond strength between base coat and insulation product (EPS) Base coat: Under dry conditions After hydrothermal cycles on the rig After freeze/thaw cycles	Ceresit CT85 ≥ 80 kPa ≥ 80 kPa Test is not required; freeze/thaw cycles not necessary		
9	Bond strength between: adhesive-substrate (concrete) Adhesives: Under dry conditions 48h immersion in water + 2h drying at (23 ± 2)*C and (50 ± 5)% RH 48h immersion in water + 7 days drying at (23 ± 2)*C and (50 ± 5)% RH	Ceresit CT83 ≥ 250 kPa ≥ 80 kPa ≥ 250 kPa		
10	Adhesion between: adhesive-thermal insulation product (EPS) Adhesives: Under dry conditions 48h immersion in water + 2h drying at (23 ± 2)*C and (50 ± 5)% RH 48h immersion in water + 7 days drying at (23 ± 2)*C and (50 ± 5)% RH	Ceresit CT83 ≥ 80 kPa ≥ 30 kPa ≥ 80 kPa		
11	Fixing strength (transverse displacement test)	Test is not required because the ETICS fulfils the criteria E * d ≤ 50,000N/mm		
12	Thermal resistance and thermal transmittance of ETICS	See Annex A 10		
13	Bond strength after ageing Rendering system: Base coat Ceresit CT85 (with the key coat) and:			

	Ceresit CT60 0,5mm, Ceresit CT710, Ceresit CT 710 Super, Ceresit CT720 + Ceresit CT721, Ceresit CT730, Ceresit CT77, Ceresit CT177, Ceresit CT760	≥ 80 kPa		
14	Characteristics of other system components			
	EPS panels	Acc. ETA-11/0395 Annex B		
	Anchors	Acc. ETA-11/0395 Annex C1		
	Glass fibre mesh Ceresit CT325	Acc. ETA-11/0395 Annex C2		

Foregoing parameters are applicable to the use of the system consisting of Ceresit Ceretherm Visage

- Adhesives: Ceresit CT83
- Base coat: Ceresit CT85
- Key coats: Ceresit CT16
- Finishing coats: Ceresit CT60 0,5mm; Ceresit CT710; Ceresit CT710 Super; Ceresit CT720; Ceresit CT730; Ceresit CT77; Ceresit CT177; Ceresit CT760
- Decorative coats: Ceresit CT721; Ceresit CT740; Ceresit CT750
- Insulation product: EPS panels acc. EN 13163; (see ETA-11/0395 Annex B for product characteristics)
- Anchors: acc. ETA-11/0395 Annex C1 for product characteristics
- Glass fiber meshes: Ceresit CT 325 (see ETA-11/0395 Annex C2 for product characteristics)

8. Appropriate Technical Documentation
and/or Specific Technical Documentation: Not relevant

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

Joanna Jarzyna
Chemist Product Development
AC Global PD Fasade Systems

Piotr Urynek
Quality Manager CEE North

(name and function)

(name and function)

(signature)

(signature)

Stąporków, 15.11.2023

(place and date of issue)