



DECLARATION OF PERFORMANCE No. 01831

1. Unique identification code of the product-type: Ceresit CL 50
2. Intended use/es: The Ceresit CL 50 kit is intended to be used in indoor applications, where is not exposed to temperatures below 5°C and above 40°C, in the following uses.
3. Manufacturer: Henkel Polska Operations Sp. z o.o., ul. Domaniewska 41, 02-672 Warszawa, Polska
- It is produced in the following manufacturing plants: Henkel Polska Operations Sp. z o.o., Stara Góra, 26-220 Stąporków
4. Authorized representative: Not relevant
5. System/s of assessment and verification of constancy of performance: System 2+
- 6a. Harmonized standard/s: Not relevant
- 6b. European Assessment Document: EAD 030352-00-0503
- European Technical Assessment: ETA-23/0068 z 02/05/2023
- Technical Assessment Body: Instytut Techniki Budowlanej
- Notified body/ies: Instytut Techniki Budowlanej, nr 1488, Zakład Certyfikacji 1488-CPR-0690/Z
7. Declared performance/s:

No	Essential characteristics	Performance	System/s of AVCP	Harmonised technical specification
1	Reaction to fire	No performance assessed	System 2+	EAD 030352-00-0503
2	Content, emission and/or release of dangerous substances	No performance assessed		
3	Vapour permeability	$S_d = 4,3 \text{ m}$ $\mu = 4312$ Climate conditions 23°C and RH 50/93%		
4	Water tightness	Watertight		
5	Crack bridging ability	Category 2 (0,75 mm)		
6	Bond strength on concrete board	Category 2 ($\geq 0,5 \text{ MPa}$)		
7	Bond strength on gypsum board	Cohesive failure in the substrate		
8	Scratching resistance	No performance assessed		
9	Joint bridging ability	Category 2		
10	Water tightness around penetrations	Category 2: watertight		
11	Resistance to temperature	Category 2 ($\geq 0,5 \text{ MPa}$)		
12	Resistance to water	Category 2 ($\geq 0,5 \text{ MPa}$)		
13	Resistance to alkalinity	Category 2 ($\geq 0,5 \text{ MPa}$)		
14	Resistance to mechanical wear	No performance assessed		
15	Slipperiness	No performance assessed		
16	Reparability	Reparable		
17	Thickness	$1,0 \text{ mm} = 1,43 \text{ kg}/(\text{mm} \times \text{m}^2)$		
18	Durability of paint kits	Not relevant		

Foregoing parameters are applicable to the use of the system consisting of Ceresit CL 50

- Membrane: Ceresit CL 50

- Reinforcements: Ceresit CL 82, Ceresit CL 83, Ceresit CL 86, Ceresit CL 87, Ceresit CL 89, Ceresit CL 152, Ceresit CL 525,

- Adhesive: Ceresit CM 22, Ceresit CM 16, Ceresit CM 17, Ceresit CM 77, Ceresit CM 49

8. Appropriate Technical Documentation
and/or Specific Technical Documentation: Not relevant

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

Malgorzata Lipnicka
AC Global PD TG Inorganics, IDC IF / EE North
Mineral Adhesive & Coatings Manager

(name and function)

(signature)

Piotr Urynek
Quality Manager CEE North

(name and function)

(signature)

Stąporków, 22.08.2023
(place and date of issue)