

EN 12004:2007 + A1:2012

## **DECLARATION OF PERFORMANCE**

No. 00063

1.	Unique identification code of the product-typ	e: S-Line Super Flex	
2.	Intended use/es:	All internal and external tiling	
3.	Manufacturer:	Henkel Polska Operations Sp. z o.o., ul. Doman	iewska 41, 02-672 Warszawa
4.	Authorised representative:	N/A	
5.	System/s of assessment and verification of constancy of performance:	System 3	
6a.	Harmonised standard/s:	EN 12004:2007 + A1:2012	
	Notified body/ies:	Instytut Techniki Budowlanej, Zakład Badań Ogniowych no 1488	
6b.	European Assessment Document: European Technical Assessment: Technical Assessment Body: Notified body/is:	N/A N/A N/A N/A	
7.	Declared performance/s:		
	Essential characteristics	Performance	Harmonised technical specification
	Reaction to fire	A1; A1 <sub>fl</sub> Class	
	Bond strength expressed as:	Initial tensile adhesive strength ≥ 1,0 N/mm <sup>2</sup>	
	Durability of bond strength against climate/heat ageing action expressed as:	Tensile adhesion strength after heat aging ≥ 1,0 N/mm²	7

8. Appropriate Technical Documentation and/or Specific Technical Documentation:

1,0 N/mm<sup>2</sup>

1,0 N/mm<sup>2</sup>

NPD

Durability of bond strength against

water/humidity action expressed as:

Durability of bond strength against

freeze-thaw cycles expressed as:

Release of dangerous substances

Signed for and on behalf of the manufacturer by:

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Tensile adhesion strength after water immersion ≥

Tensile adhesion strength after freeze-thaw cycles ≥

Malgorzata Lipnicka Piotr Urynek AC Global PD TG Inorganics, IDC IF / EE North Quality Manager CEE North Mineral Adhesive & Coatings Manager (name and function) (name and function) (signature)

Stąporków, 28.03.2019

(place and date of issue)