

DECLARATION OF PERFORMANCE

No. 00526

1. Unique identification code of the product-type: Ceresit CF 43
2. Intended use/es: Products for surface protection - coating
3. Manufacturer: Henkel Polska Sp. z o.o., ul. Domaniewska 41, 02-672 Warszawa.
4. Authorised representative: N/A
5. System/s of assessment and verification of constancy of performance: System 3
- 6a. Harmonised standard/s: EN 1504-2:2004
Notified body/ies: Instytut Techniki Budowlanej, no 1488
- 6b. European Assessment Document: N/A
European Technical Assessment: N/A
Technical Assessment Body: N/A
Notified body/ies: N/A
7. Declared performance/s:

Essential characteristics	Performance	System/s of assessment and verification of constancy of performance	Harmonised technical specification
Reaction to fire	B _{fl} - s1	System 3	EN 1504-2:2004
Water permeability:	0,0285 kg/(m ² x h ^{0,5}) related to the limit value W < 0,1 kg/(m ² x h ^{0,5})		
Impact resistance:	Class I ≥ 4 Nm		
Pull-off resistance:	4,6 MPa; related to the limit value 1,5 MPa		
Abrasion resistance, Taber method:	291,4 mg; related to the limit value 3000 mg		
The release of volatile substances	Permitted to be applied in the rooms of category A and B after 14 days of seasoning (air)		

8. Appropriate Technical Documentation and/or Specific Technical Documentation: N/A

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

Karol Bednarczyk
Manager of ETISC
Technical Department
ACE/AC ITSC BME ETICS

Piotr Urynek
Quality Manager CEE North

(name and function)

(name and function)

(signature)

(signature)

Stąporków, 01.06.2017

(place and date of issue)