

DECLARATION OF PERFORMANCE

No. 00508

1. Unique identification code of the product-type: Ceresit CR 43
2. Intended use/es: One-coat rendering mortar for external use.
3. Manufacturer: Henkel Polska Operations Sp. z o.o., 41 Domaniewska Street, Warsaw, 02-672
4. Authorised representative: N/A
5. System/s of assessment and verification of constancy of performance: System 4
- 6a. Harmonised standard/s: EN 998-1:2016
Notified body/ies: N/A
- 6b. European Assessment Document: N/A
European Technical Assessment: N/A
Technical Assessment Body: N/A
Notified body/ies: N/A
7. Declared performance/s:

Essential characteristics	Performance	Harmonised technical specification
Reaction to fire	NPD	EN 998-1:2016
Water absorption	W_{e1}	
Water vapour permeability μ	- μ (saturated solution of KNO_3): ≤ 40 - μ (saturated solution of $LiCl$): ≤ 80	
Adhesion	$\geq 1,0$ MPa – FP:B	
Thermal conductivity $\lambda_{10, dry}$	0,47 W/mK (tabulated value)	
Durability (resistance to freezing and thawing)	- water permeability $\leq 1,0$ ml/cm ² after 48h Adhesive after seasoning cycles: - to concrete: $\geq 1,0$ MPa – FP:B - to aerated concrete: $\geq 0,3$ MPa – FP:A	
Dangerous substances.	NPD	

8. Appropriate Technical Documentation and/or Specific Technical Documentation: N/A

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

Malgorzata Lipnicka
AC Global PD TG Inorganics, IDC IF / EE North
Mineral Adhesive & Coatings Manager

Piotr Urynek
Quality Manager CEE North

(name and function)

(name and function)

(signature)

(signature)

Stąporków, 17.09.2019

(place and date of issue)