

DECLARATION OF PERFORMANCE
according Annex III of the Regulation (EU) No 305/2011

Name of the product: CERESIT MPS

No. 00701

1. Unique identification code of the product-type:

EN 15651-1: F-EXT-INT
EN 15651-2: G
EN 15651-3: S

2. Type, batch or serial number or any other element allowing identification of the construction product as required pursuant to Article 11(4):

Batch number: see packaging of the product

3. Intended use or uses of the construction product, in accordance with the applicable harmonised technical specification, as foreseen by the manufacturer:

Sealant for facade for interior and exterior application
Sealant used for sealing glazing applications
Sealant for joints in sanitary areas

4. Name, registered trade name or registered trade mark and contact address of the manufacturer as required pursuant to Article 11(5):

Henkel AG & Co. KGaA
D-40191 Düsseldorf

5. Where applicable, name and contact address of the authorised representative whose mandate covers the tasks specified in Article 12(2):

Not relevant

6. System or systems of assessment and verification of constancy of performance of the construction product as set out in Annex V:

System 3 + System 3 for the reaction to fire

7. In case of the declaration of performance concerning a construction product covered by a harmonised standard:

The notified body FUNDACION TECNALIA RESEARCH & INNOVATION, identification number 1292, performed the determination of the product-type on the basis of type testing under system 3 and issued: a test report

The notified body FUNDACION TECNALIA RESEARCH & INNOVATION, identification number 1292, performed the determination of the class regarding reaction to fire on the basis of product testing under system 3 and issued: a test report

8. In case of the declaration of performance concerning a construction product for which a European Technical Assessment has been issued:

Not relevant

9. Declared performance

Conditioning: Method A

Substrate: Aluminium without primer

| Essential characteristics | Performance | Harmonised technical specification |
|---|-------------|------------------------------------|
| Reaction to fire | Class E | EN 15651-1:2012 |
| Release of chemicals dangerous to the environment and health | NPD | EN 15651-1:2012 |
| Water tightness and air tightness | | |
| Resistance to flow | ≤ 3 mm | EN 15651-1:2012 |
| Loss of volume | ≤ 45 % | EN 15651-1:2012 |
| Tensile properties (i.e. elongation) after immersion in water at 23°C | ≥ 100 % | EN 15651-1:2012 |
| Durability | pass | EN 15651-1:2012 |

Conditioning: Method A

Substrate: Glass without primer

| Essential characteristics | Performance | Harmonised technical specification |
|---|-------------|------------------------------------|
| Reaction to fire | Class E | EN 15651-2:2012 |
| Release of chemicals dangerous to the environment and health | NPD | EN 15651-2:2012 |
| Water tightness and air tightness | | |
| Loss of volume | ≤ 40 % | EN 15651-2:2012 |
| Vertical flow resistance | ≤ 3 mm | EN 15651-2:2012 |
| Adhesion/cohesion properties after exposure to heat, water and artificial light | NF | EN 15651-2:2012 |
| Elastic recovery | ≥ 60 % | EN 15651-2:2012 |
| Durability | pass | EN 15651-2:2012 |

Conditioning: Method A

Substrate: Aluminium without primer

| Essential characteristics | Performance | Harmonised technical specification |
|---|-------------|------------------------------------|
| Reaction to fire | Class E | EN 15651-3:2012 |
| Release of chemicals dangerous to the environment and health | NPD | EN 15651-3:2012 |
| Water tightness and air tightness | | |
| Resistance to flow | ≤ 3 mm | EN 15651-3:2012 |
| Loss of volume | ≤ 40 % | EN 15651-3:2012 |
| Tensile properties (i.e. elongation) after immersion in water at 23°C | ≥ 25 % | EN 15651-3:2012 |
| Microbiological growth | 0 | EN 15651-3:2012 |
| Durability | pass | EN 15651-3:2012 |

10. The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 9. This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.

Signed for and on behalf of the manufacturer by:

Baptiste Chièze
International Brand Manager
(name and function)




(signature)

Dr. Bernhard Schöttmer
Director Global Product Development
(name and function)



(signature)

Düsseldorf, 27.05.2014
(place and date of issue)

| | |
|--|---------|
|  1292 | |
| Henkel AG & Co. KGaA, D-40191 Düsseldorf 14 00701 | |
| EN 15651-1: 2012 Sealant for facade for interior and exterior application - Type: F-EXT-INT - Conditioning: Method A - Substrate: Aluminium without primer | |
| Reaction to fire | Class E |
| Release of chemicals dangerous to the environment and health | NPD |
| Water tightness and air tightness | |
| Resistance to flow | ≤ 3 mm |
| Loss of volume | ≤ 45 % |
| Tensile properties (i.e. elongation) after immersion in water at 23°C | ≥ 100 % |
| Durability | pass |
| EN 15651-2: 2012 Sealant used for sealing glazing applications - Type: G - Conditioning: Method A - Substrate: Glass without primer | |
| Reaction to fire | Class E |
| Release of chemicals dangerous to the environment and health | NPD |
| Water tightness and air tightness | |
| Loss of volume | ≤ 40 % |
| Vertical flow resistance | ≤ 3 mm |
| Adhesion/cohesion properties after exposure to heat, water and artificial light | NF |
| Elastic recovery | ≥ 60 % |
| Durability | pass |
| EN 15651-3: 2012 Sealant for joints in sanitary areas - Type: S - Conditioning: Method A - Substrate: Aluminium without primer | |
| Reaction to fire | Class E |
| Release of chemicals dangerous to the environment and health | NPD |
| Water tightness and air tightness | |
| Resistance to flow | ≤ 3 mm |
| Loss of volume | ≤ 40 % |
| Tensile properties (i.e. elongation) after immersion in water at 23°C | ≥ 25 % |
| Microbiological growth | 0 |
| Durability | pass |