

## DECLARATION OF PERFORMANCE

No. 00701

- |   |   |
|---|---|
| 1. Unique identification code of the product-type:                      | CERESIT MPS TRANSPARENT   |
| 2. Intended use/es:   | Sealant for facade for interior and exterior application (F-EXT-INT)<br>Sealant used for sealing glazing applications (G)<br>Sealant for joints in sanitary areas (S) |
| 3. Manufacturer:  | Henkel AG & Co. KGaA<br>D-40191 Düsseldorf  |
| 4. Authorised representative:   | Not relevant  |
| 5. System/s of assessment and verification of constancy of performance: | Type-testing: System 3<br>Reaction to fire: System 3  |
| 6a. Harmonised standard/s:  | EN 15651-1:2012<br>EN 15651-2:2012<br>EN 15651-3:2012   |
| Notified body/ies:  | Type-testing: FUNDACION TECNALIA RESEARCH & INNOVATION, 1292<br>Reaction to fire : FUNDACION TECNALIA RESEARCH & INNOVATION, 1292                                     |
| 6b. European Assessment Document:                                       | Not relevant  |
| European Technical Assessment:  | Not relevant  |
| Technical Assessment Body:  | Not relevant  |
| Notified body/is:   | Not relevant  |
| 7. Declared performance/s:  |   |
| Conditioning: Method A  |   |
| Substrate: Aluminium; without primer                                    |   |

Essential characteristics	Performance	System/s of assessment and verification of constancy of performance	Harmonised technical specification
Reaction to fire	Class E	System 3	EN 15651-1:2012
Release of chemicals dangerous to the environment and health	NPD	System 3	
Water tightness and air tightness			
Resistance to flow	≤ 3 mm		
Loss of volume	≤ 45 %		
Tensile properties (i.e. elongation) after immersion in water at 23°C	≥ 100 %		
Durability	pass		

Conditioning: Method A  
Substrate: Glass; without primer

Essential characteristics	Performance	System/s of assessment and verification of constancy of performance	Harmonised technical specification
Reaction to fire	Class E	System 3	EN 15651-2:2012
Release of chemicals dangerous to the environment and health	NPD	System 3	
Water tightness and air tightness			
Loss of volume	≤ 40 %		
Resistance to flow	≤ 3 mm		
Adhesion/cohesion properties after exposure to heat, water and artificial light	NF		
Elastic recovery	≥ 60 %		
Durability	pass		

Conditioning: Method A  
Substrate: Aluminium; without primer

Essential characteristics	Performance	System/s of assessment and verification of constancy of performance	Harmonised technical specification
Reaction to fire	Class E	System 3	EN 15651-3:2012
Release of chemicals dangerous to the environment and health	NPD	System 3	
Water tightness and air tightness			
Resistance to flow	≤ 3 mm		
Loss of volume	≤ 40 %		
Tensile properties (i.e. elongation) after immersion in water at 23°C	≥ 25 %		
Microbiological growth	0		
Durability	pass		

8. Appropriate Technical Documentation and/or Specific Technical Documentation: Not relevant



The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

Baptiste Chièze  
International Brand Manager  
(name and function)

A handwritten signature in black ink, appearing to be "B. Chièze", written over a horizontal line.


(signature)

Dr. Bernhard Schöttmer  
Director Global Product Development  
(name and function)

A handwritten signature in black ink, appearing to be "B. Schöttmer", written over a horizontal line.

(signature)

Düsseldorf, 23.8.2016  
(place and date of issue)

 1292	
Henkel AG & Co. KGaA, D-40191 Düsseldorf 14 00701  CERESIT MPS TRANSPARENT	
EN 15651-1:2012 Sealant for facade for interior and exterior application - Type: F-EXT-INT - Conditioning: Method A - Substrate: Aluminium; without primer	
<b>Reaction to fire</b>	Class E
<b>Release of chemicals dangerous to the environment and health</b>	NPD
<b>Water tightness and air tightness</b>	
Resistance to flow	≤ 3 mm
Loss of volume	≤ 45 %
Tensile properties (i.e. elongation) after immersion in water at 23°C	≥ 100 %
<b>Durability</b>	pass
EN 15651-2:2012 Sealant used for sealing glazing applications - Type: G - Conditioning: Method A - Substrate: Glass; without primer	
<b>Reaction to fire</b>	Class E
<b>Release of chemicals dangerous to the environment and health</b>	NPD
<b>Water tightness and air tightness</b>	
Loss of volume	≤ 40 %
Resistance to flow	≤ 3 mm
Adhesion/cohesion properties after exposure to heat, water and artificial light	NF
Elastic recovery	≥ 60 %
<b>Durability</b>	pass
EN 15651-3:2012 Sealant for joints in sanitary areas - Type: S - Conditioning: Method A - Substrate: Aluminium; without primer	
<b>Reaction to fire</b>	Class E
<b>Release of chemicals dangerous to the environment and health</b>	NPD
<b>Water tightness and air tightness</b>	
Resistance to flow	≤ 3 mm
Loss of volume	≤ 40 %
Tensile properties (i.e. elongation) after immersion in water at 23°C	≥ 25 %
Microbiological growth	0
<b>Durability</b>	pass