

DECLARATION OF PERFORMANCE  
according Annex III of the Regulation (EU) No 305/2011

**Name of the product: UniBond All Purpose Paintable Sealant**

**No. 00888**

1. Unique identification code of the product-type:  
EN 15651-1: F-INT
2. Type, batch or serial number or any other element allowing identification of the construction product as required pursuant to Article 11(4):  
Batch number: see packaging of the product
3. Intended use or uses of the construction product, in accordance with the applicable harmonised technical specification, as foreseen by the manufacturer:  
Sealant for facade for interior application only
4. Name, registered trade name or registered trade mark and contact address of the manufacturer as required pursuant to Article 11(5):  
Henkel AG & Co. KGaA  
D-40191 Düsseldorf
5. Where applicable, name and contact address of the authorised representative whose mandate covers the tasks specified in Article 12(2):  
Not relevant
6. System or systems of assessment and verification of constancy of performance of the construction product as set out in Annex V:  
System 4 + System 4 for the reaction to fire
7. In case of the declaration of performance concerning a construction product covered by a harmonised standard:  
Not relevant
8. In case of the declaration of performance concerning a construction product for which a European Technical Assessment has been issued:  
Not relevant

9. Declared performance

Conditioning: Method B


Substrate: Aluminium without primer

Essential characteristics	Performance	Harmonised technical specification
<b>Reaction to fire</b>	Class F	EN 15651-1:2012
<b>Release of chemicals dangerous to the environment and health</b>	NPD	EN 15651-1:2012
<b>Water tightness and air tightness</b>		
Resistance to flow	≤ 5 mm	EN 15651-1:2012
Loss of volume	≤ 45 %	EN 15651-1:2012
Tensile properties (i.e. elongation) at break at 23°C	≥ 25 %	EN 15651-1:2012
<b>Durability</b>	pass	EN 15651-1:2012

10. The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 9. This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.


Signed for and on behalf of the manufacturer by:

Baptiste Chièze  
International Brand Manager  
(name and function)



(signature)


Dr. Bernhard Schöttmer  
Director Global Product Development  
(name and function)



(signature)

Düsseldorf, 06.02.2014  
(place and date of issue)

Attachment

	
Henkel AG & Co. KGaA, D-40191 Düsseldorf 14 00888	
EN 15651-1: 2012 Sealant for facade for interior application only	
- Type: F-INT - Conditioning: Method B - Substrate: Aluminium without primer	
<b>Reaction to fire</b>	Class F
<b>Release of chemicals dangerous to the environment and health</b>	NPD
<b>Water tightness and air tightness</b>	
Resistance to flow	≤ 5 mm
Loss of volume	≤ 45 %
Tensile properties (i.e. elongation) at break at 23°C	≥ 25 %
<b>Durability</b>	pass