

DECLARATION OF PERFORMANCE

No. 01191

Henkel AG & Co. KGaA

Type-testing: System 3

EN 15651-1:2012

Not relevant

Not relevant

Not relevant

Not relevant

Reaction to fire: System 3

D-40191 Düsseldorf

Not relevant

1. Unique identification code of the product-type:

UniBond Outdoor Window & Door Frame Sealant (01191)

Sealant for facade for interior and exterior application (F-EXT-INT)

- 2. Intended use/es:
- 3. Manufacturer:
- 4. Authorised representative:
- System/s of assessment and verification of constancy of performance:
- 6a. Harmonised standard/s:

Notified body/ies:

- Type-testing: SKZ-TeConA GmbH, 1213 Reaction to fire : SKZ-TeConA GmbH, 1213
- 6b. European Assessment Document: European Technical Assessment: Technical Assessment Body: Notified body/is:
- 7. Declared performance/s:

Conditioning: Method A Substrate: Aluminium; without primer

Essential characteristics	Performance	System/s of assessment and verification of constancy of performance	Harmonised technical specification
Reaction to fire	Class E	System 3	
Release of chemicals dangerous to the environment and health	NPD		
Water tightness and air tightness			
Resistance to flow	≤ 3 mm	System 3 EN 156	
Loss of volume	≤ 10 %		
Tensile properties (i.e. elongation) at maintained extension after water immersion	NF		EN 15651-1:2012
Durability			
Tensile properties (i.e. elongation) at maintained extension after water immersion	NF		

8. Appropriate Technical Documentation Not relevant and/or Specific Technical Documentation:



The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

Ian Lapsley Global Head of Marketing ACG I (name and function)

opster.

(signature)

Dr. Michael Frank Director Global Product Development (name and function)

und Ann

(signature)

Düsseldorf, 24.10.2022 (place and date of issue)



Attachment

CE				
1213				
Henkel AG & Co. KGaA				
D-40191 Düsseldorf				
16				
01191				
UniBond Outdoor Window & Door Frame Sealant (01191)				
EN 15651-1:2012				
Sealant for facade for interior and exterior application				
Reaction to fire	Class E			
Water tightness and air tightness				
Resistance to flow	≤ 3 mm			
Loss of volume	≤ 10 %			
Tensile properties (i.e. elongation) at maintained	NF			
extension after water immersion				
Durability				
Tanaila proportion (i.e. alangetian) at maintained	NF			
Tensile properties (i.e. elongation) at maintained				
extension after water immersion				