

DECLARATION OF PERFORMANCE

No. 01193

- Unique identification code of the UniBond Kitchen & Bathroom Speed Sealant 1. product-type: 2. Intended use/es: Sealant for joints in sanitary areas - EN 15651-3: S 3. Manufacturer: Henkel AG & Co. KGaA D-40191 Düsseldorf 4. Authorised representative: Not relevant System/s of assessment and Type testing: System 3 5. verification of constancy of Reaction to fire: System 3 performance: 6a. Harmonised standard/s: EN 15651-3: 2012 Notified body/ies: Type testing: SKZ Testing GmbH, 1213 Reaction to fire: SKZ Testing GmbH, 1213 6b. European Assessment Document: Not relevant European Technical Assessment: Not relevant Technical Assessment Body: Not relevant Notified body/is: Not relevant
- 7. Declared performance/s:

Conditioning: Method A Substrate: Aluminium; without primer

Essential characteristics	Performance	System/s of assessment and verification of constancy of performance	Harmonised technical specification
Reaction to fire	Class E	System 3	
Release of chemicals dangerous to the environment and health	NPD		
Water tightness and air tightness			
Resistance to flow	≤ 3 mm	System 3 EN 15651-3:20	
Loss of volume	≤ 20 %		EN 15651-3:2012
Tensile properties (i.e. elongation) at maintained extension after water immersion]	NF		
Microbiological growth	1		
Durability	pass		

8. Appropriate Technical Documentation Not relevant and/or Specific Technical Documentation:



The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

Baptiste Chièze International Brand Manager (name and function)

65

(signature)

Dr. Bernhard Schöttmer Director Global Product Development (name and function)

Bri in

(signature)

Düsseldorf, 07.12.2015 (place and date of issue)



Attachment

CE				
1213				
Henkel AG & Co. KGaA, D-40191 Düsseldorf 16 01193				
UniBond Kitchen & Bathroom Speed Sealant				
EN 15651-3: 2012				
Sealant for joints in sanitary areas - Type S - Conditioning: Method A - Substrate: Aluminium; without primer				
Reaction to fire	Class E			
Release of chemicals dangerous to the environment and health	NPD			
Water tightness and air tightness				
Resistance to flow	≤3 mm			
Loss of volume	≤ 20 %			
Tensile properties (i.e. elongation) at maintaine extension after water immersion]	d NF			
Microbiological growth	1			
Durability	pass			