

## **DECLARATION OF PERFORMANCE**

No. 01196

Unique identification code of the

product-type:

3.

**UniBond Sanitary Silicone Sealant** 

2. Intended use/es: Sealant for joints in sanitary areas - EN 15651-3: S

Manufacturer: Henkel AG & Co. KGaA

D-40191 Düsseldorf

4. Authorised representative: Not relevant

System/s of assessment and 5. verification of constancy of

performance:

Type testing: System 3 Reaction to fire: System 3

6a. Harmonised standard/s: EN 15651-3: 2012

Notified body/ies: Type testing: **FUNDACION TECNALIA** RESEARCH

INNOVATION, 1292

Reaction to fire: FUNDACION TECNALIA RESEARCH &

INNOVATION, 1292

6b. European Assessment Document:

European Technical Assessment: **Technical Assessment Body:** 

Notified body/is:

Not relevant Not relevant Not relevant

Not relevant

Declared performance/s: 7.

Conditioning: Method A

Substrate: Aluminium: without primer

Essential characteristics	Performance	System/s of assessment and verification of constancy of performance	Harmonised technical specification
Reaction to fire	Class E	System 3	
Release of chemicals dangerous to the environment and health	NPD		
Water tightness and air tightness		]	
Resistance to flow	≤ 3 mm	System 3 EN 15651-3:20°	FN 45654 2:2042
Loss of volume	≤ 40 %		EN 15051-3.2012
[Tensile properties (i.e. elongation) after immersion in water at 23°C	≥ 25 %		
Microbiological growth	0		
Durability	pass		

Appropriate Technical Documentation

and/or Specific Technical

Documentation:

Not relevant

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:



Baptiste Chièze International Brand Manager	Dr. Bernhard Schöttmer Director Global Product Development
(name and function)	(name and function)
3/	B522
(signature)	(signature)
	üsseldorf, 09.12.2015



## Attachment

CE				
1292				
Henkel AG & Co. KGaA, D-40191 Düsseldorf				
16				
01196				
UniBond Sanitary Silicone Sealant				
ombona daniary dindona dalam				
EN 15651-3: 2012				
Sealant for joints in sanitary areas				
- Type S				
- Conditioning: Method A				
- Substrate: Aluminium; without primer				
Reaction to fire	Class E			
Release of chemicals dangerous to the	NPD			
environment and health				
Water tightness and air tightness				
Resistance to flow	≤ 3 mm			
Loss of volume	≤ 40 %			
[Tensile properties (i.e. elongation) after	≥ 25 %			
immersion in water at 23°C				
Microbiological growth	0			
Durability	pass			