

DECLARATION OF PERFORMANCE

No. 01196

Unique identification code of the UniBond Sanitary Silicone Sealant Translucent 1. product-type: 2. Intended use/es: Sealant for joints in sanitary areas (S) 3. Henkel AG & Co. KGaA Manufacturer: D-40191 Düsseldorf 4. Authorised representative: Not relevant 5. System/s of assessment and Type-testing: System 3 verification of constancy of Reaction to fire: System 3 performance: 6a. Harmonised standard/s: EN 15651-3:2012 Notified body/ies: Type-testing: FUNDACION **TECNALIA** RESEARCH & INNOVATION, 1292 Reaction to fire : FUNDACION TECNALIA RESEARCH & INNOVATION, 1292 6b. European Assessment Document: Not relevant European Technical Assessment: Not relevant Technical Assessment Body: Not relevant Notified body/is: Not relevant Declared performance/s: 7.

Conditioning:	Method A	

Conditioning	j. Method /	A	
Substrate: A	luminium;	without	primer

Essential characteristics	Performance	System/s of assessment and verification of constancy of performance	Harmonised technical specification
Reaction to fire	Class E	System 3	
Release of chemicals dangerous to the environment and health	NPD		
Water tightness and air tightness			
Resistance to flow	≤ 3 mm		EN 15651-3:2012
Loss of volume	≤ 40 %	System 3	EN 19091-3.2012
Tensile properties (i.e. elongation) after immersion in water at 23°C	≥ 25 %]	
Microbiological growth	0		
Durability	pass		

 Appropriate Technical Documentation and/or Specific Technical Documentation: Not relevant



The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

Baptiste Chièze International Brand Manager (name and function)

6

(signature)

Dr. Bernhard Schöttmer Director Global Product Development (name and function)

(signature)

Düsseldorf, 23.8.2016 (place and date of issue)



Attachment

	1000	
	1292	
Henkel AG	& Co. KGaA, D-40	191 Düsseldorf
	16	
01196		
UniBond Sanitary Silicone Sealant Translucent		
	EN 15651-3:2012	
Sealant for joints in sanitary areas		
- Type	S	iy aleas
- Conditioning:	Method A	
- Substrate:	Aluminium; without primer	
Reaction to fire		Class E
Release of chemicals da	ngerous to the	NPD
environment and health		
Water tightness and air	tightness	
Resistance to flow		≤ 3 mm
Loss of volume		≤ 40 %
Tensile properties (i.e. elongation) after		≥ 25 %
immersion in water at 23	°C	
Microbiological growth		0
Durability		pass