

## DECLARATION OF PERFORMANCE

No. 01199

1. Unique identification code of the product-type: UniBond General Purpose Silicone Sealant White
2. Intended use/es: Sealant for facade for interior and exterior application (F-EXT-INT)  
Sealant for joints in sanitary areas (S)
3. Manufacturer: Henkel AG & Co. KGaA  
D-40191 Düsseldorf
4. Authorised representative: Not relevant
5. System/s of assessment and verification of constancy of performance: Type-testing: System 3  
Reaction to fire: System 3
- 6a. Harmonised standard/s: EN 15651-1:2012  
EN 15651-3:2012  
Notified body/ies: Type-testing: FUNDACION TECNALIA RESEARCH & INNOVATION, 1292  
Reaction to fire : LGAI TECHNOLOGICAL CENTER, S. A./Applus, 0370
- 6b. European Assessment Document: Not relevant  
European Technical Assessment: Not relevant  
Technical Assessment Body: Not relevant  
Notified body/is: Not relevant
7. Declared performance/s:  
Conditioning: Method A  
Substrate: Glass; without primer

| Essential characteristics  | Performance | System/s of assessment and verification of constancy of performance | Harmonised technical specification |
|--|-------------|---|------------------------------------|
| Reaction to fire   | Class E     | System 3  | EN 15651-1:2012                    |
| Release of chemicals dangerous to the environment and health                       | NPD         | System 3  |                                    |
| Water tightness and air tightness  |             |   |                                    |
| Resistance to flow   | ≤ 3 mm      |   |                                    |
| Loss of volume   | ≤ 25 %      |   |                                    |
| Tensile properties (i.e. elongation) at maintained extension after water immersion | NF          |   |                                    |
| Durability   | pass        |   |                                    |

Conditioning: Method A  
Substrate: Glass; without primer


| Essential characteristics   | Performance | System/s of assessment and verification of constancy of performance | Harmonised technical specification |
|---|-------------|---|------------------------------------|
| Reaction to fire  | Class E     | System 3  | EN 15651-3:2012                    |
| Release of chemicals dangerous to the environment and health          | NPD         | System 3  |                                    |
| Water tightness and air tightness                                     |             |   |                                    |
| Resistance to flow  | ≤ 3 mm      |   |                                    |
| Loss of volume  | ≤ 20 %      |   |                                    |
| Tensile properties (i.e. elongation) after immersion in water at 23°C | ≥ 25 %      |   |                                    |
| Microbiological growth  | 1           |   |                                    |
| Durability  | pass        |   |                                    |

8. Appropriate Technical Documentation and/or Specific Technical Documentation: Not relevant

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.


Signed for and on behalf of the manufacturer by:

Baptiste Chièze  
International Brand Manager  
(name and function)




(signature)

Dr. Bernhard Schöttmer  
Director Global Product Development  
(name and function)



(signature)

Düsseldorf, 23.8.2016  
(place and date of issue)

|   |         |
|---|---------|
| <br>1292; 0370   |         |
| Henkel AG & Co. KGaA, D-40191 Düsseldorf<br>16<br>01199<br><br>UniBond General Purpose Silicone Sealant White   |         |
| EN 15651-1:2012<br>Sealant for facade for interior and exterior application<br>- Type F-EXT-INT<br>- Conditioning: Method A<br>- Substrate: Glass; without primer |         |
| <b>Reaction to fire</b>   | Class E |
| <b>Release of chemicals dangerous to the environment and health</b>   | NPD     |
| <b>Water tightness and air tightness</b>  |         |
| Resistance to flow  | ≤ 3 mm  |
| Loss of volume  | ≤ 25 %  |
| Tensile properties (i.e. elongation) at maintained extension after water immersion  | NF      |
| <b>Durability</b>   | pass    |
| EN 15651-3:2012<br>Sealant for joints in sanitary areas<br>- Type S<br>- Conditioning: Method A<br>- Substrate: Glass; without primer                             |         |
| <b>Reaction to fire</b>   | Class E |
| <b>Release of chemicals dangerous to the environment and health</b>   | NPD     |
| <b>Water tightness and air tightness</b>  |         |
| Resistance to flow  | ≤ 3 mm  |
| Loss of volume  | ≤ 20 %  |
| Tensile properties (i.e. elongation) after immersion in water at 23°C   | ≥ 25 %  |
| Microbiological growth  | 1       |
| <b>Durability</b>   | pass    |