

RESEARCH

DECLARATION OF PERFORMANCE

No. 01200

Not relevant

1. Unique identification code of the

product-type:

UniBond Sanitary Silicone Sealant

Intended use/es:

Sealant for joints in sanitary areas - EN 15651-3: S

Manufacturer:

Henkel AG & Co. KGaA D-40191 Düsseldorf

4. Authorised representative:

System/s of assessment and

verification of constancy of performance:

Type testing: System 3 Reaction to fire: System 3

periormanoe.

5.

6a. Harmonised standard/s: EN 15651-3: 2012

Notified body/ies: Type testing: FUNDACION

INNOVATION, 1292

TECNALIA

Reaction to fire: LGAI TECHNOLOGICAL CENTER, S. A./Applus, 0370

6b. European Assessment Document:

European Technical Assessment: Technical Assessment Body: Notified body/is: Not relevant Not relevant Not relevant Not relevant

7. Declared performance/s:

Conditioning: Method A

Substrate: Glass; without primer

Essential characteristics	Performance	System/s of assessment and verification of constancy of performance	Harmonised technical specification
Reaction to fire	Class E	System 3	
Release of chemicals dangerous to the environment and health	NPD		
Water tightness and air tightness			
Resistance to flow	≤ 3 mm	System 3 EN 15651-3:2	EN 15651 2:2012
Loss of volume	≤ 20 %		EN 13031-3.2012
[Tensile properties (i.e. elongation) after immersion in water at 23°C	≥ 25 %		
Microbiological growth	1		
Durability	pass		

8. Appropriate Technical Documentation

and/or Specific Technical

Documentation:

Not relevant

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:



Baptiste Chièze International Brand Manager	Dr. Bernhard Schöttmer Director Global Product Development
(name and function)	(name and function)
3/	B522
(signature)	(signature)
	üsseldorf, 08.12.2015



Attachment

CE				
1292, 0370				
Henkel AG & Co. KGaA, D-40191 Düsseldorf 16 01200				
UniBond Sanitary Silicone Sealant				
EN 15651-3: 2012				
Sealant for joints in sanitary areas - Type S - Conditioning: Method A - Substrate: Glass; without primer				
Reaction to fire		Class E		
Release of chemicals dangerous to the environment and health		NPD		
Water tightness and air tightness				
Resistance to flow		≤ 3 mm		
Loss of volume		≤ 20 %		
[Tensile properties (i.e. elongation) after		≥ 25 %		
immersion in water at 23°C				
Microbiological growth		1		
Durability		pass		