

## **DECLARATION OF PERFORMANCE**

No. 01200

1. Unique identification code of the

product-type:

UniBond Sanitary Silicone Sealant (01200)

2. Intended use/es: Sealant for joints in sanitary areas (S)

3. Manufacturer: Henkel AG & Co. KGaA

D-40191 Düsseldorf

4. Authorised representative: Not relevant

5. System/s of assessment and verification of constancy of

performance:

Type-testing: System 3 Reaction to fire: System 3

6a. Harmonised standard/s: EN 15651-3: 2012

Notified body/ies: Type-testing: FUNDACION TECNALIA RESEARCH &

INNOVATION, 1292

Reaction to fire: LGAI TECHNOLOGICAL CENTER, S. A./Applus,

0370

6b. European Assessment Document:

European Technical Assessment: Technical Assessment Body: Notified body/is: Not relevant Not relevant Not relevant Not relevant

7. Declared performance/s:

Conditioning: Method A

Substrate: Glass; without primer

Essential characteristics	Performance	System/s of assessment and verification of constancy of performance	Harmonised technical specification
Reaction to fire	Class E	System 3	
Release of chemicals dangerous to the environment and health	NPD		
Water tightness and air tightness			
Resistance to flow	≤ 3 mm	System 3	EN 15651-3: 2012
Loss of volume	≤ 20 %		
Tensile properties (i.e. elongation) at maintained extension after water immersion	NF		
Microbiological growth	1		
Durability	pass		

8. Appropriate Technical Documentation

and/or Specific Technical

Documentation: Not relevant



The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

Ian Lapsley	Dr. Bernhard Schöttmer	
Global Head of Marketing ACG I	Director Global Product Development	
(name and function)	(name and function)	
Japsien.	BSIE	
(signature)	(signature)	
Dü	sseldorf, 14.8.2019	
(pla	ace and date of issue)	



## Attachment

Henkel AG & Co. KGaA D-40191 Düsseldorf 16 01200

UniBond Sanitary Silicone Sealant (01200)

EN 15651-3: 2012

Sealant for joints in sanitary areas S

- Type - Conditioning: - Substrate:

Method A Glass; without primer

Reaction to fire	Class E
Water tightness and air tightness	
Resistance to flow	≤ 3 mm
Loss of volume	≤ 20 %
Tensile properties (i.e. elongation) at maintained extension after water immersion	NF
Microbiological growth	1
Durability	pass

www.henkel-dop.com