

## DECLARATION OF PERFORMANCE

No. 01202

- |   |  |
|---|--|
| 1. Unique identification code of the product-type:                      | UniBond Outdoor Extreme Repair Sealant   |
| 2. Intended use/es:   | Sealant for facade for interior and exterior application - EN 15651-1: F-EXT-INT     |
| 3. Manufacturer:  | Henkel AG & Co. KGaA<br>D-40191 Düsseldorf   |
| 4. Authorised representative:   | Not relevant   |
| 5. System/s of assessment and verification of constancy of performance: | Type testing: System 3<br>Reaction to fire: System 3                                 |
| 6a. Harmonised standard/s:  | EN 15651-1: 2012   |
| Notified body/ies:  | Type testing: SKZ - Testing GmbH, 1213<br>Reaction to fire: SKZ - Testing GmbH, 1213 |
| 6b. European Assessment Document:                                       | Not relevant   |
| European Technical Assessment:  | Not relevant   |
| Technical Assessment Body:  | Not relevant   |
| Notified body/is:   | Not relevant   |
| 7. Declared performance/s:  |  |
| Conditioning: Method A  |  |
| Substrate: Aluminium; without primer                                    |  |

Essential characteristics	Performance	System/s of assessment and verification of constancy of performance	Harmonised technical specification
Reaction to fire	Class E	System 3	EN 15651-1:2012
Release of chemicals dangerous to the environment and health	NPD	System 3	
Water tightness and air tightness			
Resistance to flow	≤ 3 mm		
Loss of volume	≤ 10%		
Tensile properties (i.e. elongation) at maintained extension after water immersion]	NF		
Durability	pass		

- |   |              |
|---|--------------|
| 8. Appropriate Technical Documentation and/or Specific Technical Documentation: | Not relevant |
|---|--------------|



The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

Baptiste Chièze  
International Brand Manager  
(name and function)

A handwritten signature in black ink, appearing to be "B. Chièze", written over a horizontal line.

(signature)

Dr. Bernhard Schöttmer  
Director Global Product Development  
(name and function)

A handwritten signature in black ink, appearing to be "B. Schöttmer", written over a horizontal line.

(signature)

Düsseldorf, 19.01.2016

(place and date of issue)

Attachment

 <b>1213</b>	
Henkel AG & Co. KGaA, D-40191 Düsseldorf 16 1202  UniBond Outdoor Extreme Repair Sealant	
EN 15651-1: 2012  Sealant for facade for interior and exterior application - Type F-EXT-INT - Conditioning: Method A - Substrate: Aluminium; without primer	
<b>Reaction to fire</b>	Class E
<b>Release of chemicals dangerous to the environment and health</b>	NPD
<b>Water tightness and air tightness</b>	
Resistance to flow	≤ 3 mm
Loss of volume	≤ 10%
Tensile properties (i.e. elongation) at maintained extension after water immersion]	NF
<b>Durability</b>	pass