



DECLARATION OF PERFORMANCE

No. 01216

- | | |
|---|--|
| 1. Unique identification code of the product-type: | Unibond Indoor Flexible Decorators Filler |
| 2. Intended use/es: | Sealant for facade for interior application only - EN 15651-1: F-INT |
| 3. Manufacturer: | Henkel AG & Co. KGaA
D-40191 Düsseldorf |
| 4. Authorised representative: | Not relevant |
| 5. System/s of assessment and verification of constancy of performance: | Type testing: System 4
Reaction to fire: System 4 |
| 6a. Harmonised standard/s: | EN 15651-1: 2012 |
| Notified body/ies: | Not relevant |
| 6b. European Assessment Document: | Not relevant |
| European Technical Assessment: | Not relevant |
| Technical Assessment Body: | Not relevant |
| Notified body/is: | Not relevant |

7. Declared performance/s:

Conditioning: Method A

Substrate: Aluminium; without primer

Essential characteristics	Performance	System/s of assessment and verification of constancy of performance	Harmonised technical specification
Reaction to fire	Class F	System 4	EN 15651-1:2012
Release of chemicals dangerous to the environment and health	NPD	System 4	
Water tightness and air tightness			
Resistance to flow	≤ 5 mm		
Loss of volume	≤ 45 %		
Tensile properties (i.e. elongation) at break at 23°C	≥ 25 %		
Durability	pass		

8. Appropriate Technical Documentation and/or Specific Technical Documentation: Not relevant



The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

Baptiste Chièze
International Brand Manager

(name and function)

A handwritten signature in black ink, appearing to be "B. Chièze", written over a horizontal line.

(signature)

Dr. Bernhard Schöttmer
Director Global Product Development

(name and function)

A handwritten signature in black ink, appearing to be "B. Schöttmer", written over a horizontal line.

(signature)

Düsseldorf, 08.01.2016
(place and date of issue)

Attachment

CE	
Henkel AG & Co. KGaA, D-40191 Düsseldorf 16 01216 Unibond Indoor Flexible Decorators Filler	
EN 15651-1: 2012	
Sealant for facade for interior application only	
- Type	F-INT
- Conditioning:	Method A
- Substrate:	Aluminium; without primer
Reaction to fire	Class F
Release of chemicals dangerous to the environment and health	NPD
Water tightness and air tightness	
Resistance to flow	≤ 5 mm
Loss of volume	≤ 45 %
Tensile properties (i.e. elongation) at break at 23°C	≥ 25 %
Durability	pass