

DECLARATION OF PERFORMANCE

No. 01226

1. Unique identification code of the

product-type:

UniBond FT101 Sealant

2. Intended use/es:

Sealant for facade for interior and exterior application - EN 15651-

1: F-EXT-INT

Not relevant

3. Manufacturer:

Henkel AG & Co. KGaA D-40191 Düsseldorf

4. Authorised representative:

System/s of assessment and verification of constancy of

performance:

Type testing: System 3 Reaction to fire: System 3

6a. Harmonised standard/s: EN 15651-1: 2012

Notified body/ies: Type testing: SKZ Testing GmbH, 1213

Reaction to fire: SKZ Testing GmbH, 1213

6b. European Assessment Document:

European Technical Assessment: Technical Assessment Body:

Notified body/is:

Not relevant Not relevant Not relevant Not relevant

7. Declared performance/s:

Conditioning: Method A

Substrate: Aluminium; without primer

Essential characteristics	Performance	System/s of assessment and verification of constancy of performance	Harmonised technical specification
Reaction to fire	Class E	System 3	
Release of chemicals dangerous to the environment and health	NPD		
Water tightness and air tightness			
Resistance to flow	≤ 3 mm	System 3 EN 15651-1:	EN 15651 1:2012
Loss of volume	≤ 10 %		EN 13031-1.2012
Tensile properties (i.e. elongation) at maintained extension after water immersion]	NF		
Durability	pass		

8. Appropriate Technical Documentation

and/or Specific Technical

Documentation:

Not relevant



The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

Baptiste Chièze	Dr. Bernhard Schöttmer
International Brand Manager	Director Global Product Development
(name and function)	(name and function)
3/	13512
(signature)	(signature)
D	üsseldorf, 03.02.2016
	place and date of issue)



Attachment

CE				
1213				
Henkel AG & Co. KGaA, D-40191 Düsseldorf				
16				
01226				
UniBond FT101 Sealant				
EN 15651-1: 2012				
Sealant for facade for interior and exterior application - Type F-EXT-INT				
- Conditioning: Method A				
- Substrate: Aluminium; without primer				
Reaction to fire	Class E			
Release of chemicals dangerous to the environment and health	NPD			
Water tightness and air tightness				
Resistance to flow	≤ 3 mm			
Loss of volume	≤ 10 %			
Tensile properties (i.e. elongation) at maintained extension after water immersion	NF			
Durability	pass			