

## DECLARATION OF PERFORMANCE

No. 01720

1. Unique identification code of the product-type: Pattex Sanitary (01720)
2. Intended use/es: Sealant for facade for interior and exterior application (F-EXT-INT)  
Sealant for joints in sanitary areas (S)
3. Manufacturer: Henkel AG & Co. KGaA  
D-40191 Düsseldorf
4. Authorised representative: Not relevant
5. System/s of assessment and verification of constancy of performance: Type-testing: System 3  
Reaction to fire: System 3
- 6a. Harmonised standard/s: EN 15651-1:2012  
EN 15651-3:2012
- Notified body/ies: Type-testing: FUNDACION TECNALIA RESEARCH & INNOVATION, 1292  
Reaction to fire : FUNDACION TECNALIA RESEARCH & INNOVATION, 1292
- 6b. European Assessment Document: Not relevant  
European Technical Assessment: Not relevant  
Technical Assessment Body: Not relevant  
Notified body/is: Not relevant
7. Declared performance/s:

Conditioning: Method A

Substrate: Aluminium; without primer

Substrate: Aluminium, without primer			
Essential characteristics	Performance	System/s of assessment and verification of constancy of performance	Harmonised technical specification
Reaction to fire	Class E	System 3	EN 15651-1:2012
Release of chemicals dangerous to the environment and health	NPD	System 3	
Water tightness and air tightness			
Resistance to flow	≤ 3 mm		
Loss of volume	≤ 45 %		
Tensile properties (i.e. elongation) after immersion in water at 23°C	≥ 100 %		
Durability			
Tensile properties (i.e. elongation) after immersion in water at 23°C	≥ 100 %		

Conditioning: Method A  
Substrate: Aluminium; without primer


Essential characteristics	Performance	System/s of assessment and verification of constancy of performance	Harmonised technical specification
Reaction to fire	Class E	System 3	EN 15651-3:2012
Release of chemicals dangerous to the environment and health	NPD	System 3	
Water tightness and air tightness			
Resistance to flow	≤ 3 mm		
Loss of volume	≤ 40 %		
Tensile properties (i.e. elongation) after immersion in water at 23°C	≥ 25 %		
Microbiological growth	0		
Durability			
Tensile properties (i.e. elongation) after immersion in water at 23°C	≥ 25 %		

8. Appropriate Technical Documentation Not relevant  
and/or Specific Technical  
Documentation:

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

Ian Lapsley  
Global Head of Marketing ACG I  
(name and function)




(signature)

Dr. Michael Frank  
Director Global Product Development  
(name and function)



(signature)

Düsseldorf, 16.12.2021  
(place and date of issue)

 1292	
Henkel AG & Co. KGaA D-40191 Düsseldorf 22 01720  Pattex Sanitary (01720)	
EN 15651-1:2012 Sealant for facade for interior and exterior application	
<b>Reaction to fire</b>	Class E
<b>Water tightness and air tightness</b>	
Resistance to flow	≤ 3 mm
Loss of volume	≤ 45 %
Tensile properties (i.e. elongation) after immersion in water at 23°C	≥ 100 %
<b>Durability</b>	
Tensile properties (i.e. elongation) after immersion in water at 23°C	≥ 100 %
EN 15651-3:2012 Sealant for joints in sanitary areas	
<b>Reaction to fire</b>	Class E
<b>Water tightness and air tightness</b>	
Resistance to flow	≤ 3 mm
Loss of volume	≤ 40 %
Tensile properties (i.e. elongation) after immersion in water at 23°C	≥ 25 %
Microbiological growth	0
<b>Durability</b>	
Tensile properties (i.e. elongation) after immersion in water at 23°C	≥ 25 %
www.henkel-dop.com	