



**DECLARATION OF PERFORMANCE  
according Annex III of the Regulation (EU) No 305/2011**

Name of the product: **Ceresit CM 16**

**No 00030**

1. Unique identification code of the product-type: **EN 12004 C2TES1**
2. Type, batch or serial number or any other element allowing identification of the construction product as required pursuant to Article 11(4):

**Batch number: see packaging of the product**

3. Intended use or uses of the construction product, in accordance with the applicable harmonised technical specification, as foreseen by the manufacturer:

**Improved deformable cementitious adhesive with reduced slip and extended open time**

4. Name, registered trade name or registered trade mark and contact address of the manufacturer as required pursuant to Article 11(5):

**Henkel Romania srl , Ionita Vornicu 1-7 street , 020325, District 2, Bucharest**

5. Where applicable, name and contact address of the authorised representative whose mandate covers the tasks specified in Article 12(2):

**not relevant**

6. System or systems of assessment and verification of constancy of performance of the construction product as set out in Annex V:

**System 3**

7. In case of the declaration of performance concerning a construction product covered by a harmonised standard:

The notified testing laboratory **ICECON CERT NB 1803**, performed the determination of the product-type on the basis of the type testing under system 3 and issued a test report.

8. In case of declaration of performance concerning a construction product for which a European Technical Assessment has been issued:

**not relevant**

9. Declared performance

Essential characteristic	Performance	Harmonised technical specification
<b>Bond strength as</b>		EN 12004:2007+A1:2012
Initial tensile adhesion strength	$\geq 1,0 \text{ N/mm}^2$	
<b>Durability of bond strength as</b>		
Tensile adhesion strength after water immersion	$\geq 1,0 \text{ N/mm}^2$	
Tensile adhesion strength after heat ageing	$\geq 1,0 \text{ N/mm}^2$	
Tensile adhesion strength after frost-thaw cycles	$\geq 1,0 \text{ N/mm}^2$	
Deformable adhesive: transverse deformation	$\geq 2.5 \text{ mm} < 5 \text{ mm}$	
Extended open time: Tensile adhesion strength after not less than 30 min.	$\geq 0.5 \text{ N/mm}^2$	
Slip	$\leq 0,5 \text{ mm}$	
Reaction to fire	Class F	
Release of dangerous substances	see MSDS	

Where pursuant to Article 37 or 38 the Specific Technical Documentation has been used, the requirements with which the product complies:

**not applicable**

10. The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 9. This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.

Signed for and on behalf of the manufacturer by:

QC Manager  
Aurora Dragolici

Bucharest, 03.08.2016

Regional PD AC EE South Manager  
Emilia Duta