

DECLARATION OF PERFORMANCE

١.	Unique identification code of the product-type	: CERESIT CT 35			
2.	Intended use/es:	Coloured rendering and plastering	a mortar for oxtorn	al and internal use	
3.	Manufacturer:				
	. 0	Henkel Polska Operations Sp. z o	.o., ul. Domaniewsl	ka 41, 02-672 Warszav	
1.	Authorized representative:	Not relevant			
5.	System/s of assessment				
	and verification of constancy of performance:	System 4			
За.	Harmonized standard/s:	EN 998-1:2016			
	Notified body/ies:	Not relevant			
Sb.	European Assessment Document:	Not relevant			
	European Technical Assessment:	Not relevant			
	Technical Assessment Body:	Not relevant			
	Notified body/ies:	Not relevant			
7.	Declared performance/s:				
	Essential characteristics	Performance	System/s of AVCP	Harmonised technical specification	
	Reaction to fire	Class A1		EN 998-1:2016	
	Adhesion	≥ 0,25 N/mm² – FP:B			
	Water absorption	Wc 2			
	Water vapour permeability µ	≤ 30			
	Thermal conductivity λ _{10,dry} Durability (resistance to freezing and thawing	0,54 W/m*K (tabulated value.)			
	Adhesion change	g) ≤ 19.4 %			
		Agree with requirements. See MSDS			
3.	Appropriate Technical Documentation and/or Specific Technical Documentation:	Not relevant			

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

Dagmara Kwiatkowska AC Global PD TG Facade Systems, IDC ETICS ETICS Manager	Piotr Urynek Quality Manager CEE North
(name and function) The afleoushe	(name and function)
(signature)	(signature)
Stąport	ków, 10.01.2018
(place a	and date of issue)